



TACKIFIERS · HOW TO USE

ECO-TAC - PAM TACKIFIER

Professional-grade PAM (polyacrylamide) tackifier - a sodium acrylate/acrylamide copolymer that dissolves quickly, lubricates the slurry through your gun, binds mulch to soil, and controls dust. A cost-effective bonding option for erosion-prone jobs.

WHEN TO USE IT

- Cost-effective bonding for erosion jobs
- Slurry lubricant through the gun
- Dust control

HOW TO MIX & APPLY

- 1 Confirm the job first - site, slope, soil condition, seed, and machine (jet or mechanical).
- 2 Fill the tank with water, then load your mulch and bring it to a uniform slurry.
- 3 Add TurfBlaster® Eco-Tac per the current product label and keep agitation up so it mixes in evenly.
- 4 Apply a complete, even pass and overlap your edges. Add a tackifier on slopes or ahead of weather before germination.
- 5 Water in and keep the surface moist through germination, per your seed and site.

RATES & COVERAGE

Function	Tackifier · slurry lubricant · dust control
Dissolves	Quickly in the tank
Coverage	~2 acres per case

PRO TIP

Build the slurry in the right order and keep agitation up - even mixing is what gives you an even, uniform stand.

Always follow the current product label for application rates, mixing order, and handling. For job-specific guidance, ask the New Turf team or Sprout at hydroseed.ai. Order through [Hydroseed Supply](https://hydroseedsupply.com) (hydroseedsupply.com).

TB-ECO-TAC-APP-v2 · TurfBlaster® is manufactured by Turf Blasters Products, LLC and distributed by Hydroseed Supply. TurfBlaster®, TurfBlasters® and "Kickin' Some Serious Grass!®" are registered trademarks of New Turf Ventures, Inc., used under license. Powered by Turf Blasters® Mycelium III.