

MULCH & FIBER · HOW TO USE

100% WOOD FIBER HYDROMULCH

100% virgin wood fiber that runs clean in mechanical and hydraulic machines - the one crews reach for first, on lawns, commercial turf, and erosion jobs alike.



WHEN TO USE IT

- Quality residential & commercial lawns
- Slopes where staying power matters
- Runs clean in mechanical and jet machines

HOW TO MIX & APPLY

- 1 Confirm the job first - site, slope, soil condition, seed, and machine (jet or mechanical).
- 2 Fill the tank with water, then load your mulch and bring it to a uniform slurry.
- 3 Add TurfBlaster® 100% Wood Fiber Hydromulch per the current product label and keep agitation up so it mixes in evenly.
- 4 Apply a complete, even pass and overlap your edges. Add a tackifier on slopes or ahead of weather before germination.
- 5 Water in and keep the surface moist through germination, per your seed and site.

RATES & COVERAGE

Coverage **~50 lb per 1,000 sq ft**

PRO TIP

Build the slurry in the right order and keep agitation up - even mixing is what gives you an even, uniform stand.

POUNDS, NOT GALLONS

Load mulch by weight, not tank volume. Your machine's working mulch capacity (not its water gallons) sets how much ground a load actually covers.

Always follow the current product label for application rates, mixing order, and handling. For job-specific guidance, ask the New Turf team or Sprout at hydroseed.ai. Order through **Hydroseed Supply** (hydroseedsupply.com).